



CERT

DIN-DVGW type examination certificate

DIN-DVGW-Baumusterprüfzertifikat

NW-1412BN0621

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	DK-Kälteanlagen GmbH Hollefeldstr. 30, D-48282 Emsdetten
Distributor <i>Vertreiber</i>	DK-Kälteanlagen GmbH Hollefeldstr. 30, D-48282 Emsdetten
Product Category <i>Produktart</i>	Water heaters: Storage water heater, indirectly heated with intermediate medium heat exchanger (1412)
Product description <i>Produktbezeichnung</i>	Intermedia heat exchanger application outside from drinking water tanks
Model <i>Modell</i>	R-Rohrenhitzer/Rohrkondensator/Wärmetauscher
Test reports <i>Prüfberichte</i>	Laboratory control test: from 15.06.2023 (TSD) Type testing: IS-DDK-MUC/bu from 28.01.2013 (TSD)
Test basis <i>Prüfgrundlagen</i>	DIN 4753-1 (01.11.2011) DVGW W 517 (01.05.2012)



70026-04_A.DE

Date of Expiry / File No. 14.11.2027 / 23-0346-WNV
Ablaufdatum / Aktenzeichen

15.08.2023 LE A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

20.7.23



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-01

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
54/4 x 16/10	Operating pressure: drinking water up to 10 bar	
64/4 x 16/10; 64/7 x 16/10	Operating pressure: drinking water up to 10 bar	
76/6 x 16/10; 76/7 x 16/10	Operating pressure: drinking water up to 10 bar	
89/10 x 16/10; 89/14 x 16/10	Operating pressure: drinking water up to 10 bar	
108/14 x 16/10; 108/21 x 16/10	Operating pressure: drinking water up to 10 bar	
133/20 x 16/10; 133/28 x 16/10	Operating pressure: drinking water up to 10 bar	
159/28 x 16/10; 159/38 x 16/10	Operating pressure: drinking water up to 10 bar	
219/48 x 16/10; 219/64 x 16/10	Operating pressure: drinking water up to 10 bar	
267/72 x 16/10	Operating pressure: drinking water up to 10 bar	

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

The intermedia heat exchanger is usable at drinking water tanks in the sizes of 300, 450, 750, 1000, 1500, 2000, 3000, 5000 and 7000 litres.