









Spare parts

Illustration	Description	Order no.
	Cover for inspection hole and seal 110 mm round 120 mm round <i>if enamel on flat face is poss. defective a full-face seal can be supplied incl. of new screws 8x25</i>	S31906 & S31907 S31908 & S31909
	Cover for inspection hole with sleeve 12 mm and seal 110 mm round 120 mm round (if magnesium anode available)	S31906 & S31907 S31908 & S31909
	Cover for inspection hole and seal 100/150 mm Cover for inspection hole and seal 80/120 mm for reservoir with magnesium anode with 12 mm sleeve	S31902 & S31900 S31903 & S31901
	Flange cover and seal DN 200 for heat recovery storage with side flange Hole circle: 245/12x16 mm	S31650 & S31600
	Flange gasket DN 200 For heat recovery storage with bottom flange Hole circle: 245/12x14 mm	S31602
	Flange gasket DN 200 for chilled water reservoir Hole circle: 245/12x16 mm	S31601

Spare parts

Illustration	Description	Order no.
	<p>Manhole gasket DN 500 610 x 500 x 3 / hole circle 565/32x18 mm</p> <p><i>for older product lines DN 450 (570 x 450 x 3 / hole circle 520/28 x 23 mm) gaskets can also be supplied</i></p> <p>- dimensions must be measured on site!</p>	<p>S31700</p> <p>S31701</p>
	<p>CORREX® External Current Anode incl. plug-in potentiostat for heat recovery vessels for chilled water vessels</p> <p>CORREX® External Current Anode incl. 2 probe elements incl. dual cable for heat recovery systems</p>	<p>S39016 S39017</p> <p>S39021</p>
	<p>Magnesium Anodes with external thread for vessels with bottom flange for vessels 120/1 for vessels 200/1 for vessels 300/1 and 500/1</p>	<p>S31100 S31200 S31300</p>
	<p>Magnesium Anodes with M 12 setscrew for vessels with side flange for vessels 300/4 (one anode) for vessels 500/4 (one anode) for vessels 750/5 (two anodes) for vessels 1000/5 (two anodes)</p>	<p>S31400 S31500 S31400 & S31200 S31500 & S31300</p>
	<p>Thermometer 0-120°C for heat recovery vessels</p>	<p>S39027</p>
	<p>Angled Thermometer -30/+50°C for chilled water vessel</p>	<p>S39028</p>

Spare parts

Illustration	Description	Order no.
	Boiler Thermostat Switching range +25° to +90°C	S39007
	Electrical heater for Enamelled Vessels incl. fitted thermostat Model kW 2.0 Model kW 3.0 Model kW 4.5 Model kW 6.0 Thermostat loose	S37030 S30445 S37033 S37041 S39034
	Overheating-prevention-thermostat required when fitting electrical heating	S39035
	Electrical heater for Raw Vessels incl. thermostat and safety limiter Model kW 2.0 Model kW 3.0 Model kW 4.5 Model kW 6.0 Model kW 9.0	S39036 S39037 S39038 S39039 S39040
	Ranco Anti-freezing Thermostat (2.0) for chilled water vessel	S39041
	3-Way Valve 3-way mixing valve 3/4" 3-way mixing valve 1" 3-way mixing valve 1 1/2" Temperature probe for 3-way valve	S55803 S55805 S55804 S60084